



RODS*

Diameter	Wt. Per Ft.	Std. Lgth. (in.)
0.0625	0.003	72
0.1250	0.007	72
0.1875	0.015	72
0.2500	0.026	72
0.3125	0.042	72
0.3750	0.056	72
0.4375	0.081	72
0.0500	0.100	72
0.6250	0.158	72
0.7500	0.227	72
0.8750	0.309	72
1.0000	0.403	72
1.1250	0.511	72
1.2500	0.630	72
1.3750	0.762	72
1.5000	1.000	72
1.7500	1.260	72
2.0000	1.646	72
2.5000	2.560	72



HALF ROUND STRIPS

Diameter	Wt. Per Ft.	Std. Lgth. (in.)
0.05	0.05	72
0.625	0.08	72
0.75	0.114	72
1.0	0.203	72



RECTANGLE STRIPS

Sizes		Wt. Per Ft.	Std. Lgth. (in.)
A	B		
0.125	0.375	0.025	72
0.125	0.625	0.043	72
0.25	0.5	0.02	72
0.187	0.75	0.08	72
0.25	1.0	0.14	72
0.75	1.0	0.406	72



TUBING*

Sizes		Wt. Ft./Lb.	Std. Lgth. (in.)	Wall Tol. (±)
O.D.	I.D.			
0.25	0.125	52.6	72	0.01
0.313	0.187	38.5	72	0.01
0.375	0.25	31.2	72	0.01
0.375	0.125	19.6	72	0.01
0.5	0.375	22.7	72	0.01
0.5	0.25	13.2	72	0.01
0.625	0.5	17.2	72	0.01
0.625	0.375	10.0	72	0.01
0.75	0.625	14.3	72	0.01
0.75	0.5	7.8	72	0.01
0.875	0.75	12.0	72	0.01
0.875	0.625	6.6	72	0.01
1.0	0.875	10.5	72	0.01
1.0	0.75	5.6	72	0.01
1.25	1.125	8.3	72	0.01
1.25	1.0	4.4	72	0.015
1.375	1.125	4.0	72	0.015
1.5	1.25	3.6	72	0.015
1.625	1.375	3.3	72	0.015
1.75	1.5	3.0	72	0.015
2.0	1.75	2.6	72	0.015
2.25	2.0	2.3	72	0.015
2.5	2.25	2.0	72	0.02
2.75	2.5	1.9	72	0.02
3.0	2.75	1.37	72	0.02
3.25	3.0	1.6	72	0.025
3.5	3.25	1.5	72	0.025
3.75	3.5	1.4	72	0.025
4.0	3.75	1.3	72	0.03
4.5	4.25	1.1	72	0.03
5.0	4.75	1.0	72	0.04
6.0	5.75	0.84	72	0.05



SQUARE RODS

Size	Wt. Per Ft.	Std. Lgth. (in.)
0.125	0.008	72
0.187	0.16	72
0.25	0.033	72
0.375	0.73	72
0.05	0.13	72
0.625	0.206	72
0.75	0.3	72
1.0	0.55	72



TRIANGLE STRIPS

Sizes	Wt. Per Ft.	Std. Lgth. (in.)
0.25	0.017	72
0.375	0.04	72
0.5	0.005	72
0.625	0.103	72
0.075	0.75	72
1.0	0.225	72



SQUARE TUBE

Sizes		Wt. Per Ft.	Std. Lgth. (in.)
O.D.	I.D.		
0.375	0.25	0.06	72
0.05	0.375	0.056	72
0.625	0.5	0.072	72
0.75	0.625	0.088	72
1.0	0.875	0.12	72

Offers Extraordinary Transparency, Exceptional Durability, Resistance to Heat Exposure, and Good Mechanical Strength

Acrylic Sheet

- Available clear, a variety of colors, white, green edged
- Thicknesses 1/16 to 3"
- Extruded or cast
- Matte finish, UV filtering, non glare available, UVA, UVT
- Standard sheet size is 4 ft x 8 ft . Many other sheet sizes
- Mirror sheet
- Scratch resistant coating
- Clean with proper materials(no Windex type products)

Specifications

ASTM D-702 ANSI Z97.1-1872

L-P-391 NSF FDA

Mil-P24191 UL 94 HB

Mil-P-8184

Mil-P-5425

Fabrication

Cutting,Routing,Drilling,Machining,Edge Finishing,Polishing